

How Do I remove Wallpaper?

Q&A

What are the tools that I will need to remove wallpaper?

Wallpaper remover such as CHOMP, wallpaper scraping tool, spray bottle, putty knife, sponge, stepladder & drop cloth

How long do I have to wait after I have applied wallpaper remover to begin the removal process?

Generally, thirty minutes to an hour is sufficient time to allow the remover to soak in and loosen the wallpaper paste.

What do I do if the wallpaper pulls off the face of the sheetrock?

Some slight wall damage can be normal however, if you are experiencing an excessive amount of damage, STOP IMMEDIATELY and call a professional.

I have removed the patterned paper from the walls but it left a yellow, fuzzy paper.....what is that?

What you have is a solid sheet vinyl product and it is in fact a two step process. Step one is to remove the face (patterned area). You will be left with a yellow, fuzzy finish which is the backing paper. Step two is to apply the wallpaper remover and then scrape that backing off the walls.

How do I get the wallpaper paste off of the wall after the wallpaper is removed?

Once you have removed the wallpaper from the walls, you must then reapply the remover and scrape off excess leftover paste. You will also want to use dish detergent and water to do a final wash making sure that when you run your hand over the wall it is smooth and free of residue.

Once I have removed the wallpaper and am ready to hang my new paper, what do I need to do to the walls? Am I ready to go since they were prepped before?

It is always best to apply a clear wallpaper sizing to the walls prior to any wallpaper installation. Omitting this step will produce a nightmare in the future.